


Двухручьевые матрицы 90°

SR.AD55.90.07

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD55.90.10

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD55.90.12

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD50.90.10

700 kN/m max.


835 mm	8.2 kg
415 mm	4.0 kg



SR.AD50.90.12

800 kN/m max.

835 mm	8.2 kg
415 mm	4.0 kg




Двухручьевые матрицы 88°

SR.AD55.88.10

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD55.88.12

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD55.88.20

1000 kN/m max.


835 mm	9.2 kg
415 mm	4.6 kg



SR.AD55.88.25

1000 kN/m max.


835 mm	8.2 kg
415 mm	4.0 kg



SR.AD55.88.18

1000 kN/m max.


835 mm	8.2 kg
415 mm	4.0 kg



SR.AD55.88.20

1000 kN/m max.


835 mm	7.6 kg
415 mm	3.8 kg



SR.AD50.88.10

700 kN/m max.


835 mm	8.2 kg
415 mm	4.0 kg



SR.AD50.88.12

800 kN/m max.


835 mm	8.2 kg
415 mm	4.0 kg



SR.AD50.88.18

1000 kN/m max.


835 mm	7.8 kg
415 mm	3.8 kg



SR.AD50.88.20

1000 kN/m max.

835 mm	7.8 kg
415 mm	3.8 kg



SR.AD50.88.25

700 kN/m max.

835 mm	7.2 kg
415 mm	3.5 kg

